




Specifications con't

		Part Numbers	BNF10SW	BNF10NW	BNF10DW
Specifications	<b>Appearance</b>				
	<b>Width</b>		0.591" (15mm)	0.591" (15mm)	0.591" (15mm)
	<b>Blown Fuse Indicator</b>		None	Neon (100–300VAC)	LED (24V DC)
	<b>Approvals</b>		UL, CSA, Voltage 600V	UL, CSA, Voltage 600V	UL, CSA, Voltage 600V
	<b>No. of Poles</b>		1	1	1
	<b>Wire Sizes</b>		18 to 10 AWG (5.5mm <sup>2</sup> )	18 to 10 AWG (5.5mm <sup>2</sup> )	18 to 10 AWG (5.5mm <sup>2</sup> )
	<b>Current</b>		10A maximum	10A maximum	10A maximum
	<b>Terminals</b>	Size	M4	M4	M4
		Type	Standard screw	Standard screw	Standard screw
	<b>Mounting</b>		35mm DIN rail	35mm DIN rail	35mm DIN rail
	<b>Terminal Torque</b>	(N-m)	1.4 - 2.0	1.4 - 2.0	1.4 - 2.0
		(in-lbs.)	12.4 - 17.8	12.4 - 17.8	12.4 - 17.8
	<b>End Plate</b>		BNE20	BNE20	BNE20
	<b>DIN Rail Stop</b>		BNL-5	BNL-5	BNL-5
	<b>Dust Cover</b>		—	—	—
<b>Marking Strip</b>		BNM7	BNM7	BNM7	
<b>Applicable Fuse Size</b>		1/4" x 1-1/4" (6.35 x 31.8mm)	1/4" x 1-1/4" (6.35 x 31.8mm)	1/4" x 1-1/4" (6.35 x 31.8mm)	



1. BNDN1000 aluminum DIN rails are available in 1 meter lengths.
2. Fuses not included.

Dimensions

BNH Series

Part No.	Diagrams			
BNH10W BNH15MW BNH15LW	<p><b>BNH10W</b></p>	<p><b>BNH15MW</b></p>	<p><b>BNH15LW</b></p>	
	<p><b>BNH30W</b></p>	<p><b>BNH50W</b></p>		

BN Series

Part No.	Diagrams	
BN75W BN150W	<p><b>BN75W</b></p>	<p><b>BN150W</b></p>

Part No.	Diagrams
BNF10SW BNF10NW BNF10DW	
BNDH15W	

Terminal Blocks