

Surge Strips

LEVITON®

5100, 5200, S1000 & S2000 Series

LEVITON
LIFETIME LIMITED DOWNLINE
WARRANTY

SPECIFICATIONS & FEATURES

- All mode protection with clamping profile that tightly tracks AC sine wave.
- Protected outlets.
- Resettable circuit breaker and internal fusing.
- 6-foot, 14-3 AWG power cord and can be wall mounted.

ENVIRONMENTAL

STORAGE TEMPERATURE
-35°C to 60°C

OPERATING TEMPERATURE
0°C to 40°C

STANDARDS & CERTIFICATIONS

ANSI/IEEE Categories A & B
C-62.41 & C-62.45

UL 1449, 1363, 1283
#E146315

CSA
#LR-94773



5100-IPS



S1000-PS



S2000-PS

DESCRIPTION	CATALOG NO.	APPLICATION
5100, 5200, S1000, S2000 Series		
4-Outlet, General Duty, 15A 125V AC, Beige, Metal Enclosure, 6' Cord	5100-P	Compatible w/ UPS and SPS Systems
6-Outlet, General Duty, 15A 120V AC, Beige, Metal Enclosure, 6' Cord	5100-IPS	Compatible w/ UPS and SPS Systems
6-Outlet, General Duty, 20A 125V AC, Beige, Metal Enclosure, 6' Cord	5100-IS2	Compatible w/ UPS and SPS Systems
6-Outlet, Heavy Duty, 15A 125V AC, w/ON/OFF Switch, Beige, Metal Enclosure, 15' Cord	5200-PS	For Micro Processor Based Equipment
6-Outlet, Heavy Duty, 15A 125V AC, w/ON/OFF Switch, Beige, Metal Enclosure, 15' Cord	5200-S15	For Micro Processor Based Equipment
6-Outlet, General Duty, 15A 120V, Beige, Plastic Enclosure, 6' Cord	S1000-PS	General Purpose, Office
6-Outlet, Coax & RJ-11Telco, General Duty, 15A 120V, Beige, Plastic Enclosure, 6' Cord	S1000-PTC	General Purpose, Office, Velcro Mounting Strips included
9-Outlet, General Duty, 15A 120V, Beige, Plastic Enclosure, 6' Cord	S2000-PS	General Purpose, Office
9-Outlet, Coax & RJ-45Telco, General Duty, 15A, 120V, Beige, Plastic Enclosure, 6' Cord	S2000-PTC	General Purpose, Office, Velcro Mounting Strips included

CATALOG NO.	JOULES	UL 1449 (2.5 Edition) IMPULSE 6kV/500A	MAX.SURGE CURRENT (test w/ 8x20µs wave)	NOISE REJECTION (@1MHZ-100MHZ)
5100-P	720	L-N: 400V	L-N: 24kA	-10 to -40 dB
5100-IPS	900	L-N: 400V	L-N: 45kA	-10 to -40 dB
5100-IS2	900	L-N: 400V	L-N: 45kA	-10 to -40 dB
5200-PS	900	L-N: 330V	L-N: 24kA	-10 to -40 dB
5200-S15	900	L-N: 330V	L-N: 24kA	-10 to -40 dB
S1000-PS	1010	L-N: 400V	L-N: 25kA	-10 to -40 dB
S1000-PTC	1010	L-N: 400V	L-N: 25kA	-10 to -40 dB
S2000-PS	2020	L-N: 400V	L-N: 67.5kA	-10 to -40 dB
S2000-PTC	2020	L-N: 400V	L-N: 67.5kA	-10 to -40 dB

Power Quality Devices – Surge Strips