



5300 Series – 15A 120V AC Plug-In Devices



5300-HTS

SPECIFICATIONS & FEATURES

5300 SERIES

- Clamping profile tightly tracks AC sine wave.
- Six protected outlets with ON/OFF switch.
- Resettable circuit breaker and internal fusing.
- Equipped with a 6-foot 14-3 AWG power cord.

ENVIRONMENTAL

STORAGE TEMPERATURE
-35°C to 60°C

OPERATING TEMPERATURE
-10°C to 60°C

STANDARDS & CERTIFICATIONS

ANSI/IEEE Categories A & B
C-62.41 & C-62.45

UL 1449 2.5 Edition
#E146315

CSA
#LR-94773

DESCRIPTION	CATALOG NO.	APPLICATION
5300 Series		
6-Outlet w/ Switch, Beige, 6' Cord	5300-PS	Data-Sensitive Operations
6-Outlet w/ Switch, Beige, 6' Cord	5300-PST	Telephone/Modem Line Protection
6-HG, Tamper-Resistant 15A Outlets w/o Switch, Beige, Steel Enclosure, 6' Cord	5300-HTS <i>Transparent Plug</i>	Continues to supply power to load if protection is lost
6-HG, Tamper-Resistant 20A Outlets w/o Switch, Beige, Steel Enclosure, 6' Cord	5300-HT2 <i>Transparent Plug</i>	Continues to supply power to load if protection is lost
6-Outlet w/ ON/OFF Switch, Beige, 6' Cord, Metal Enclosure	5300-IPS	Rugged Aluminum Housing for use in rough environments

CATALOG NO.	JOULES	UL 1449 2.5 Edition IMPULSE 6kV/500A	MAX.SURGE CURRENT (test w/ 8x20µs wave)	NOISE REJECTION (@100K-100MHZ)	LOW VOLTAGE CLAMPING (UL 497A/B or UL 452)
5300 Series					
5300-PS	1620	L-N: 330V	L-N: 24kA	-20 to -40 dB	-
5300-PST	1620	L-N: 330V	L-N: 24kA	-20 to -40 dB	270V
5300-HTS	1080	L-N: 400V	L-N: 51kA	-20 to -40 dB	-
5300-HT2	1080	L-N: 400V	L-N: 51kA	-20 to -40 dB	-
5300-IPS	1440	L-N: 330V	L-N: 84kA	-20 to -40 dB	-