



## 5300 Series – 15A 120V AC Plug-In Devices



5300-HTS

### SPECIFICATIONS & FEATURES

#### 5300 SERIES

- Clamping profile tightly tracks AC sine wave.
- Six protected outlets with ON/OFF switch.
- Resettable circuit breaker and internal fusing.
- Equipped with a 6-foot 14-3 AWG power cord.

### ENVIRONMENTAL

**STORAGE TEMPERATURE**  
-35°C to 60°C

**OPERATING TEMPERATURE**  
-10°C to 60°C

### STANDARDS & CERTIFICATIONS

**ANSI/IEEE Categories A & B**  
C-62.41 & C-62.45

**UL 1449 2.5 Edition**  
#E146315

**CSA**  
#LR-94773

DESCRIPTION	CATALOG NO.	APPLICATION
<b>5300 Series</b>		
6-Outlet w/ Switch, Beige, 6' Cord	5300-PS	Data-Sensitive Operations
6-Outlet w/ Switch, Beige, 6' Cord	5300-PST	Telephone/Modem Line Protection
6-HG, Tamper-Resistant 15A Outlets w/o Switch, Beige, Steel Enclosure, 6' Cord	5300-HTS <i>Transparent Plug</i>	Continues to supply power to load if protection is lost
6-HG, Tamper-Resistant 20A Outlets w/o Switch, Beige, Steel Enclosure, 6' Cord	5300-HT2 <i>Transparent Plug</i>	Continues to supply power to load if protection is lost
6-Outlet w/ ON/OFF Switch, Beige, 6' Cord, Metal Enclosure	5300-IPS	Rugged Aluminum Housing for use in rough environments

CATALOG NO.	JOULES	UL 1449 2.5 Edition IMPULSE 6kV/500A	MAX.SURGE CURRENT (test w/ 8x20µs wave)	NOISE REJECTION (@100K-100MHZ)	LOW VOLTAGE CLAMPING (UL 497A/B or UL 452)
<b>5300 Series</b>					
5300-PS	1620	L-N: 330V	L-N: 24kA	-20 to -40 dB	-
5300-PST	1620	L-N: 330V	L-N: 24kA	-20 to -40 dB	270V
5300-HTS	1080	L-N: 400V	L-N: 51kA	-20 to -40 dB	-
5300-HT2	1080	L-N: 400V	L-N: 51kA	-20 to -40 dB	-
5300-IPS	1440	L-N: 330V	L-N: 84kA	-20 to -40 dB	-