

# Terminal blocks

## UK universal terminal blocks

### Connectors for disconnect terminal blocks in the UK series

- The fuse plug ST-SI-UK 4 for 5 x 20 mm cartridge fuse inserts is available with and without a LED display
- The component connector ST-BE is available as an individual connector for two-pos. components and as a double connector



Fuse plug for 5 x 20 mm cartridge fuses



Component connector for 2 and 4-pos. components

Notes:
1) If the fuse is faulty, the downstream circuit is not off load.
2) Integrated: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 1.0 A
3) With single arrangement.
4) Integrated: Rectifier module B 250 C 1500, reverse voltage: 600 V, nominal voltage: 250 V, nominal current: 1.5 A



Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm <sup>2</sup> ]
Rated cross section	[mm <sup>2</sup> ]
Cross section range	AWG
General data	
Tightening torque	[Nm]
Insulating material	PA
Inflammability class according to UL 94	V2

Technical data				
IEC	UL	CSA	IEC/ EN 60079-7	
250	300	300	-	-
6.3	6.3 / -	10 / -	-	-
-	-	-	-	-
-	-	-	-	-

Technical data				
IEC	UL	CSA	IEC/ EN 60079-7	
-	300	-	-	-
16	10 / -	-	-	-
-	-	-	-	-
-	30-14	-	-	-

Description	Color
<b>Fuse plug</b> , for cartridge fuse inserts 5 x 20 mm, 26.5 mm high, max 6.3 A	black
<b>Fuse plug</b> , for cartridge fuse inserts, 5 x 20 mm, 26.5 mm high, max. 6.3 A, with LED display, for 5-15 V AC/DC <sup>1)</sup>	black
With LED for 15-30 V AC/DC	black
With LED for 30-60 V AC/DC	black
With LED for 110-250 V AC/DC	black
<b>Component connector</b> , for switching on 2-pos. components into the basic terminal block, fixing at screw terminal points, 19 mm high, max 16 A <sup>3)</sup>	gray
<b>Component connector</b> , to connect 2-pos. components into the basic terminal block, 19 mm high, with LED for 24 V AC/DC	gray
With LED for 230 V AC/DC	gray
<b>Component connector</b> , to connect 2-pos. components into the basic terminal block, with diode 1N 4007, 19 mm high <sup>2)</sup>	gray
<b>Component plug</b> , for 4-pos. components, two basic terminal blocks required per plug, 19 mm high	gray
<b>Component plug</b> , for 4-pos. components, two basic terminal blocks required per plug, with bridge rectifier B 250 C 1500, 19 mm high <sup>4)</sup>	gray
<b>Isolating plug</b> , 13.5 mm high, max. 16 A	gray

Ordering data		
Type	Order No.	Pcs. / Pkt.
ST-SI-UK 4	0921011	50
ST-SILED 12-UK 4	0921024	50
ST-SILED 24-UK 4	0921037	50
ST-SILED 60-UK 4	0921040	50
ST-SILA250-UK 4	0921053	50

Ordering data		
Type	Order No.	Pcs. / Pkt.
ST-BE	2802316	10
ST-BE-LA 24	2802374	10
ST-BE-LA230	2802387	10
ST-1N4007	2802329	10
ST-BE-VP	2802332	10
ST-B250C1500	2802345	10
ST-K 4	5025462	50

Accessories	
<b>Plug pliers</b> , simplify removing the isolating plug from a closed row of terminal blocks	
<b>Center groove marking</b>	

Accessories		
Type	Order No.	Pcs. / Pkt.
TZ	0306704	10
ZB 6 (see Catalog 5)		

Accessories		
Type	Order No.	Pcs. / Pkt.
TZ	0306704	10
ZB 6 (see Catalog 5)		