

## OTTA 6-T



Terminal width 11

(IEC) flexible [mm <sup>2</sup> ]	stranded	AWG	I [A]	U [V]
--------------------------------------	----------	-----	----------	----------

Connection data 0.1-6 26-10 41 800 \*

Cable lug connection M4 max. external ø 9.6 mm



\* The nominal voltage applies to insulated cable lugs.

# CAF

BV/LR

Description	Color	Type	Order No.	Pcs. Pkt.
<b>Terminal block</b> , with universal foot with cable lug connection M4	gray	OTTA 6-T	<del>07 90 44 6</del> 0711276	50
<b>Terminal block</b> , as above, however, 4 mm Ø test socket screws	gray	OTTA 6-T-P/P	<del>07 90 46 2</del> 0706993	50

### Accessories

(1) <b>End cover</b>	gray		<b>D-OTTA 6-T</b>	<b>07 90 45 9</b>	50
(2) <b>Insertion bridge</b> , divisible, fully insulated,	3-pos.		<b>EB 3-OTTA 6</b>	$I_{max.}$ : 41 A <b>30 26 03 6</b>	10
	4-pos.		<b>EB 4-OTTA 6</b>	41 A <b>30 26 04 9</b>	10
	7-pos.		<b>EB 7-OTTA 6</b>	41 A <b>30 26 05 2</b>	10
	10-pos.		<b>EB 10-OTTA 6</b>	41 A <b>07 90 42 0</b>	10
(5) <b>Zack strip</b> , 10-section	white		<b>ZB 10</b> (see <a href="#">info</a> )		
(6) <b>Screwdriver</b>			<b>SZS 1,0 x 6,5</b>	<b>12 05 07 9</b>	10

### Technical data

#### Dimensions

Width / length / end cover width	[mm]	11 / 69 / 1.5
Height (NS 35:7.5 / NS 35:15 / NS 32)	[mm]	52 / 59.5 / 57

#### Technical data in accordance with IEC/ DIN VDE

Maximum load current / cross section	[A] / [mm <sup>2</sup> ]	41 / 6
Max. cross section with insertion bridge (solid / stranded)	[mm <sup>2</sup> ]	6 / 6
Rated surge voltage / contamination class	[kV] / –	8 / 3
Surge voltage category / insulation material group	– / –	III / I

group

**Ring cable lugs acc. to DIN 46234/46237**

Terminal bolt / hole diameter / width - / [mm] / [mm] M 4 / 4.3 / max. 9.6 ø

**Torque** [Nm] 1.5 - 1.8

**Color code** red/ blue / yellow

**Disconnect slide**

Thread / torque - / [Nm] M 4 / 1.5 - 1.8

**Insulation material** PA

Inflammability class acc. to UL 94 V2

Temperature indices RTI / Ti 125 / 100

**Approval data (UL and CSA)**

Nom. voltage / nom. current / conduc. sizes UL: [V] / [A] 600 / 30 / -

CSA: [V] / [A] / AWG 600 / 25 / 22 - 10

**Block diagram**

