

Single Phase, TEFC

1/3 thru 10 Hp

NEMA 56 thru 215T

Applications: Wide variety of agri-duty and industrial applications.



Features: Ball bearings, lubricated with high temperature moisture-resistant grease. Condensation drains, gasketed cast conduit boxes. Farm Duty epoxy paint protects motor from harsh environments.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot Mounted											
1/3	1800	56	FDL3501M	351	K	11.35	23	60	115/230	3	30
1/2	1800	56	FDL3504M	412	K	11.97	28	68	115/230	3.7	30,52
3/4	1800	56	FDL3507M	486	K	13.35	38	74	115/230	4.4	52
1	1800	56H	FDL3510M	552	K	12.93	40	67	115/230	6.5	30,52
		143T	FDL3510TM	552	L1	13.31	38	67	115/230	6.5	30,52
1 1/2	1800	56H	FDL3514M	622	K	13.81	48	75.5	115/230	9	2,52
		145T	FDL3514TM	622	L1	14.19	48	75.5	115/230	9	2,52
C-Face, Foot Mounted											
1/3	1800	56C	CFDL3501M	475	K	11.35	24	60	115/230	3	30
1/2	1800	56C	CFDL3504M	545	K	11.97	29	68	115/230	3.7	30,52
3/4	1800	56C	CFDL3507M	635	K	13.35	37	74	115/230	4.4	52
1	1800	56CH	CFDL3510M	719	K	13.25	38	67	115/230	6.5	30,52
1 1/2	1800	56CH	CFDL3514M	810	K	14.12	48	75.5	115/230	9	2,52
2	1800	56CHZ	CFDL3516TM	1,029	K	14.19	53	78	230	8.3	1,52
C-Face, Footless											
1/3	1800	56C	VFDL3501M	457	K	11.35	23	60	115/230	3	30
1/2	1800	56C	VFDL3504M	526	K	11.97	28	68	115/230	3.7	30,52
3/4	1800	56C	VFDL3507M	613	K	13.35	38	74	115/230	4.4	52
1	1800	56C	VFDL3510M	696	K	13.25	39	67	115/230	6.5	30,52
1 1/2	1800	56C	VFDL3514M	790	K	14.12	47	75.5	115/230	9	2,52
Foot Mounted, Extra High Torque											
2	1800	56HZ	FDL3516TM	885	K	14.19	51	78	230	8.3	1,52
		182T	FDL3611TM	994	L1	16.55	75	75	115/230	14	2,52
		184	FDL3611M	1,021	L1	15.68	75	75	115/230	14	2,52
3	1800	184	FDL3610M	1,215	L1	17.18	89	80	230	15.5	2,20,52
		184T	FDL3610TM	1,185	L1	18.05	93	80	230	15.5	2,20,52
		184T	FDL3619TM	951	L1	16.54	81	81.5	230	13.2	2,20,52
5	1800	184T	FDL3612TM	1,245	L1	18.05	99	80	230	23	2,20,52
		215	FDL3731M	1,529	L1	18.64	125	84	230	20.5	2,20,52
7 1/2	1800	213	FDL3732M	1,764	L1	18.65	142	84	230	30	2,20,52
		213T	FDL3733TM	1,622	L1	19.02	139	84	230	30	2,20,52
10	1800	215T	FDL3712TM	1,784	L1	20.77	160	84	230	40	2,20,52,89
		215T	FDL3737TM	1,901	L1	21.27	162	86.5	230	39	2,20,52,89
C-Face, Footless, Extra High Torque											
2	1800	145TC	VFDL3516TM	1,027	L1	14.19	52	78	230	8.3	1,52
3	1800	184TC	VFDL3610TM	1,392	L1	18.05	97	80	230	15.5	2,20,52
5	1800	184TC	VFDL3612TM	1,704	L1	18.33	98	80	230	23	2,20,52

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors
 Definite Purpose Motors
 Unit Handling Motors
 Brake Motors
 200 & 575 Volt Motors
 IEC Frame Motors
 50 Hertz Motors
 Inverter/Vector Motors & Controls
 DC Motors and Controls
 Soft Starters & Dynamic Brakes

**Grain Dryer/
Centrifugal Fan,
Single and
Three Phase,
TEFC and ODP**

5 thru 50 Hp

NEMA 184TZ thru 326TZ

Applications: High pressure grain drying and storage for commercial and farm applications.

Features: Shaft length is 1" longer than NEMA standard. Screens to protect against entry of trash, snakes and rodents. Three phase ratings meet EPAct efficiencies.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Single Phase, Open Drip Proof											
5	1800	184TZ	GDL1605T	1,367	L1	19.06	98	80	230	22.5	2,20
7 1/2	1800	215TZ	GDL1607T	1,797	L1	22.57	161	82.5	230	32	1
10	1800	215TZ	GDL1610T	2,080	L1	22.85	164	84	230	40	2,20
16	1800	256TZ	GDL1615T	3,095	L1	24.19	288	86.5	230	62	2,20
Three Phase, Open Drip Proof											
5	1800	184TZ	GDM3218T	755	L1	16.00	69	87.5	208-230/460	6.9	
7 1/2	1800	213TZ	GDM3311T	1,072	L1	18.00	92	88.5	208-230/460	10	
10	1800	215TZ	GDM3313T	1,300	L1	17.32	129	89.5	208-230/460	13.4	
15	1800	254TZ	GDM2513T	1,600	L1	21.00	172	91	208-230/460	19	1
20	1800	254TZ	GDM2515T	2,107	L1	23.25	165	91.7	230/460	24	30
25	1800	284TZ	GDM2531T	2,588	L1	24.44	329	91.7	230/460	31	30
30	1800	284TZ	GDM2535T	3,011	L1	25.94	351	92.4	230/460	36	30
Three Phase, Totally Enclosed Fan Cooled											
3	1800	182TZ	GDM3611T	757	L1	16.14	59	84	208-230/460	4.1	1
5	1800	184TZ	GDM3615T	876	L1	17.55	77	85.5	208-230/460	6.6	1
7 1/2	1800	213TZ	GDM3710T	1,116	L1	18.90	115	89.5	208-230/460	10.1	1
10	1800	215TZ	GDM3714T	1,801	L1	20.03	139	89.5	208-230/460	13.5	1
15	1800	254TZ	GDM2333T	2,381	L1	22.07	231	89.5	208-230/460	18.9	1
20	1800	256TZ	GDM2334T	2,549	L1	23.83	322	91	230/460	25	1,30
25	1800	284TZ	GDM4103T	3,628	L1	26.93	322	92.4	230/460	29	1,30
30	1800	286TZ	GDM4104T	4,284	L1	26.93	322	92.4	230/460	36	1,30
40	1800	324TZ	GDM4110T	5,689	L1	31.39	485	93	230/460	47	1
50	1800	326TZ	GDM4115T	5,893	L1	31.28	552	91	230/460	60	1,30

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes

**Grain Dryer/Vane
Axial Fan,
Single and
Three Phase,
TEAO and OPAO**

1.5 thru 15 Hp

NEMA 145TZ thru 215Z

Applications: Vane axial fan crop dryers.

Features: Shaft 3/4" longer than NEMA standard, shaft keyed, drilled and tapped with internal 1/4-20 tap 1" deep. Thermostats. Epoxy paint.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Single Phase, Totally Enclosed Air Over											
1.5-3	3600	145TZ	UCLE153	907	L1	14.25	52	85.5	230	12.5	1,30
3-4.5	3600	145TZ	UCLE3145	929	L1	15.62	60	82.5	230	12.5	2,20
5-7.5	3600	182TZ	UCLE570	1,132	L1	16.88	94	84	230	20.5	2,8
7.5-10	3600	182TZ	UCLE7510	1,223	L1	16.88	92	85.5	230	38	2,20,30
Single Phase, Open Air Over											
1.5-3	3600	145TZ	UCL153	825	L1	14.25	51	77	230	13.6	2,20
3-4.5	3600	145TZ	UCL3145	877	L1	15.62	60	77.8	230	14.3	2,20
		182Z	UCL345	914	L1	14.88	70	74	230	22	2,20
5-7.5	3600	182TZ	UCL570	1,080	L1	16.88	93	80	230	35	2,20
7.5-10	3600	182TZ	UCL710	1,158	L1	16.88	92	85	230	31	2,20
7.5-10.5	3600	215Z	UCL7510	1,467	L1	17.44	105	81	230	37	2,20
10-15	3600	215Z	UCL1015	1,862	L1	17.81	134	84	230	44	2,20
Single Phase, Totally Enclosed Air Over											
10-15	3600	215Z	UCLE1015	1,896	L1	18.56	160	89	230	46	2,20
Three Phase, Totally Enclosed Air Over											
1.5-3	3600	145TZ	UCME153	638	L1	13.37	42	80	208-230/460	4.1	2,20
3-4.5	3600	143TZ	UCME3145	674	L1	13.37	45	84.5	208-230/460	6	2,8
		182Z	UCME345	720	L1	14.88	65	85.5	208-230/460	6	2,20
5-7.5	3600	184TZ	UCME570	847	L1	15.38	66	84	230/460	9	2,20,30
7.5-9.2	3600	184TZ	UCME759	993	L1	16.88	85	89.5	208-230/460	8.5	2,20
7.5-10	3600	184TZ	UCME7510	993	L1	16.88	82	86.5	230/460	11.5	2,20,30
10-14	3600	215Z	UCME1014	1,268	L1	16.69	120	87.5	208-230/460	16.5	2,20
Three Phase, Open Air Over											
1.5-3	3600	145TZ	UCM153	558	L1	13.37	39	80	208-230/460	4.1	2,20
3-4.5	3600	143TZ	UCM3145	625	L1	13.37	42	81.5	208-230/460	6	2,20
		182Z	UCM345	650	L1	14.25	54	84	208-230/460	5.8	2,20
5-7.5	3600	184TZ	UCM575	798	L1	15.38	64	84	230/460	9.5	2,20
10-15	3600	184TZ	UCM713	955	L1	16.88	86	84	208-230/460	12	2
		215Z	UCM1014	1,228	L1	16.69	101	85.5	208-230/460	18	2,20

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors
 Definite Purpose Motors
 Unit Handling Motors
 Brake Motors
 200 & 575 Volt Motors
 IEC Frame Motors
 50 Hertz Motors
 Inverter/Vector Motors & Controls
 DC Motors and Controls
 Soft Starters & Dynamic Brakes

**Universal Crop Dryer, 3 thru 15 Hp
Single Phase,
PSC (switchless),
TEAO and OPAO**

NEMA 184Z thru 215Z

Applications: Specifically engineered for use on vane axial fan crop dryers.

Features: TEAO design prevents entrance of rodents, insects and other foreign matter. High full load efficiency for reduced operating cost. No mechanical switch to wear. No noise and vibration from regeneration. Less sensitive to voltage variations. Soft start. Thermostats. Epoxy paint. 1.00 Service Factor.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Totally Enclosed Air Over											
3-4.5	3600	184Z	UCCE345	925	L1	14.88	72	82	230	13	2,20
5-7.5	3600	184TZ	UCCE570	1,066	L1	16.88	83	84	230	19	2,20
7.5-9.2	3600	184TZ	UCCE759	1,174	L1	16.88	90	85.5	230	29	2,20
7.5-10.5	3600	215Z	UCCE7510	1,477	L1	17.44	106	84	230	30	2,20
13	3600	215Z	UCCE130	1,866	L1	18.57	140	85	230	50	2,20
Open Air Over											
5-7.5	3600	184TZ	UCC5700	968	L1	15.38	71	79	230	19.5	2,20
7.5-10	3600	184TZ	UCC7100	1,064	L1	16.88	80	85.5	230	28	2,20
10-15	3600	215Z	UCC10150	2,011	L1	18.57	128	83	230	41	2,20

(a) See notes on inside back flap and pages 5-6.

**Irrigation
Tower Drive,
Three Phase, TENV**

1 Hp

NEMA 56

Applications: Irrigation tower drive motors.



Features: Sealed fit at endplates. Sheds water. Conduit box cast into front endplate. Epoxy paint. High overload capabilities. The "P" indicates less pulley endplate for integral mounting; can be field modified for older designs with internal thru bolts. Operable at 50/60 Hz.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
No Endplate, Footless											
1	1800	56YZ	IM3540A-P	595	K	11.02	38	79	460	1.8	2,19,60
C-Face, Footless											
1	1800	56C	IM3540A	613	K	13.27	41	79	460	1.8	2,19,60

(a) See notes on inside back flap and pages 5-6.

Gearboxes not included in price.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes

**Auger Drive,
Single Phase,
TEFC, Flange Mount,
Capacitor Start**

1/3 thru 1-1/2 Hp

NEMA 56N Flange

Applications: Poultry feed auger drive systems.

Features: Mechanical protection of centrifugal switch to prevent damage to motor in case of overspeed. Manual reset thermal protection mounted in oversize conduit box. Farm Duty epoxy paint and thermal cover protect motor from harsh environments. Extended shaft (fan end) with wrench flats for manual jogging of auger. NEMA 56N flange connects to the drive/gear box assembly. Gear reducer is assembled to motor. High efficiency design. Moisture resistant 200°C copper windings. Stator and steel frame dipped and baked in 100% solid polyester non-hygroscopic varnish. Heavy duty Type 1 capacitor.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/3	1800	48YZ	ANFL3501M	439	K	12.44	24	60	115/230	3	30
1/2	1800	48YZ	ANFL3504M	492	K	12.44	28	68	115/230	3.7	30
3/4	1800	48YZ	ANFL3507M	575	K	13.32	35	74	115/230	4.1	30
1	1800	56YZ	ANFL3510M	709	K	13.55	41	67	115/230	6.5	30
1 1/2	1800	56YZ	ANFL3514M	1,054	K	14.43	47	75.5	115/230	9	2,30

(a) See notes on inside back flap and pages 5-6.

**Grain Stirring,
Single Phase, TEFC,
Foot Mounted**

1-1/2 Hp

NEMA 56Z

Applications: Inside bin grain stirring systems.

Features: Corrosion resistant epoxy finish, slotted fan cover designed to prevent clogging. Manual thermal with cover.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1 1/2	1800	56Z	GSL3509M	653	K	12.29	42	79	230	7.5	2,20

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes

**Instant Reversing,
Single Phase,
TEFC, Foot Mounted**

3/4 thru 2 Hp

NEMA 56 thru 184

Applications: Farm applications such as barn cleaners, bulk feeders and industrial applications.

Features: Farm Duty epoxy paint protects motor from harsh environments. Manual thermal with cover mounted in conduit box for protection, ball bearings, condensation drains, heavy-gauge steel construction.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
3/4	1800	56	IR3507M	541	K	13.25	37	65	230	5.2	2
1	1800	56	IR3510M	587	K	13.25	40	65	230	6.2	1
1 1/2	1800	184	IR3603M	1,171	L1	15.68	65	69	230	10	
2	1800	184	IR3605M	1,218	L1	15.68	75	71	230	11.5	

(a) See notes on inside back flap and pages 5-6.

**Aeration Fan,
Single and
Three Phase,
TEAO, Foot Mounted**

3/4 thru 3 Hp

NEMA 56 thru 145TZ

Applications: Aeration fans for farm grain storage, exhaust fans, air handling systems, etc.

Features: Lubrication fittings on NEMA T frames for easy on-site maintenance, ball bearings, corrosion protected with epoxy finish. Normally-closed thermostats on three phase motors.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Single Phase											
3/4	3600	56Z	AFL3520A	335	K	11.59	25	71	115/230	5.5	2
1	3600	56	AFL3521A	395	K	12.68	38	66	115/230	6	2
1 1/2	3600	56	AFL3525A	512	K	12.68	42	70	115/230	8.3	2,30
		143TZ	AFL3522A	548	L1	12.74	43	70	115/230	8.3	2,30
2	3600	143TZ	AFL3523A	669	L1	13.61	50	74	115/230	11.5	2
3	3600	145TZ	AFL3524A	698	L1	13.61	51	78	230	15	2
Three Phase											
3/4	3600	56Z	AFM3528	340	K	10.97	21	74	230/460	1.3	30
1	3600	56Z	AFM3529	369	K	10.97	23	75.5	230/460	1.8	30
1 1/2	3600	143T	AFM3530	427	L1	11.74	31	75.5	208-230/460	2.3	
3	3600	145T	AFM3532	565	L1	12.74	49	82.5	208-230/460	3.8	2

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes

Dairy/Vacuum Pump, Single Phase, TEFC, Foot Mounted **5 thru 10 Hp**

NEMA 213T thru 215T

Applications: Vacuum pumps used in the dairy industry.



Features: Manual thermal overload protected, heavy-gauge steel frame. 1.15 Service Factor. 50°C ambient-continuous duty. Farm duty epoxy paint.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
5	1800	213T	DEL3708TM	1,897	L1	19.01	132	81	230	21.2	1
7 1/2	1800	215T	DEL3733TM	2,489	L1	20.77	162	85	230	28	1
10	1800	215T	DEL3737TM	3,040	L1	20.77	162	86.5	230	39	8,89

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes