

# Industrial Networks

Panduit® Industrial Network solutions provide a reliable end-to-end network physical layer infrastructure from the enterprise to the edge. A comprehensive range of products ensures fast, repeatable, and high-quality installations to simplify robust industrial network deployment.



- Industrially rated copper and fiber cabling and connectivity is available in many performance levels and configurations, offering flexibility and fast installations for structured and point-to-point applications
- IndustrialNet™ M12 Overmolded Cordsets deliver fast, reliable connections from machines and devices to Ethernet switches and enclosures on the plant floor
- The Pre-Configured Micro Data Center (MDC) provides a secure and protected environment for active equipment and physical media when connecting enterprise and plant floor networks
- Network Zone Systems and Pre-Configured Industrial Distribution Frames (IDF) deploy Ethernet networks from machine-to-machine with fast implementation
- The no-battery, maintenance-free Industrial Network Uninterruptible Power Supply (UPS) supports industrial switches during power outages with up to 40% decreased downtime risk compared to battery-based devices

B1

## IndustrialNet™ Copper Cable for Category 5e, Category 6, and Category 6A Ethernet

B2

- Cable has been tested by an independent laboratory and complies with the electrical standard requirements of ISO11801 and ANSI/TIA-568.2-D
- UL Approved
- Industrial rated cable for reliable performance in harsh environments
- Descending length cable markings enable easy identification of remaining cable which reduces installation time and cable scrap
- Packaged on a reel

B3

C1



ISFCH6X04ATL-UG\*

C2



IUC6C04ABL-CEG

C3



ISX6004AYL-LED

C4



ISFCH5C04ATL-XG

D1



ISFCH5C02ATL-XG

D2



ISFX5502ATL-LED

D3

E1

E2

E3

E4

E5

F

G

H

Part Number	Part Description	Min. Order Qty. (MOQ)*	Min. Order Increment (MOI)*	UOM
ISFCH6X04ATL-UG	Category 6A, 4-pair, 24 AWG stranded, SF/UTP, industrial 600 V, (CMX), Teal.	10000	1000	Ft.
ISFCH6X04BTL-UG	Category 6A, 4-pair, 26 AWG stranded, SF/UTP, industrial 600 V, (CMX), Teal.			
IUC6C04ABL-CEG	Category 6, 4-pair, 24 AWG stranded, U/UTP, flame-retardant (CM) Black.	6	1	Reel
ISX6004AYL-LED	Category 6, 4-Pair, 24 AWG stranded, S/FTP, industrial high flex, flame retardant, Yellow.	12	12	Reel
ISFCH5C04ATL-XG	Category 5e, 4-pair, 24 AWG stranded, SF/UTP, 600 V high flex, flame-retardant (CM/CMX), Teal.	9000	1000	Ft.
ISFCH5C02ATL-XG	Category 5e, 2-pair, 24 AWG stranded, SF/UTP, 600 V high flex, flame-retardant (CM/CMX), Teal.			
ISFX5502ATL-LED	Category 5e, 2-pair, 24 AWG stranded, SF/UTP, industrial high flex, flame-retardant (CM/CMX), Teal.	6	1	Reel
IFRH6C04BL-UG	Category 6, 4-pair, 23 AWG solid, F/UTP, industrial 600 V, (CMR), Black.	5000	1000	Ft.
IFRH5C04BL-UG	Category 5e, 4-pair, 24 AWG solid, F/UTP, industrial 600 V, (CMR), Black.	9000	1000	Ft.

\*MOQ needs to be met prior to MOI. Contact Customer Service for additional information. For additional colors, refer to [www.panduit.com](http://www.panduit.com).

**IndustrialNet™ RJ45 Copper Patch Cords for Category 5e and Category 6 Ethernet**

- Patch cords have been tested by an independent laboratory and comply with the electrical standard requirements of IEC 60603-7 and ANSI/TIA-568.2-D
- Variant 1 bulkhead patch cords meet IP67 when mated to IP67 IndustrialNet™ Connectors
- UL Approved
- Industrial rated patch cord for reliable performance in harsh environments
- 600 V rated patch cords provide reliable performance for panel or on-machine applications when space is shared with 600 V high voltage power cables



ISTPHCH1MTL



ISTPCH1MBLY,  
ISPTH6X1MTL,  
ISTPSP1MBL,  
IUTPCH3BLY,  
IUTPSP3BL

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
ISTPHCH1MTL	Category 5e, 600 V 24 AWG stranded SF/UTP patch cord, RJ45 plug to RJ45 plug, 1m, Teal.	1	10
ISTPCH1MBLY	Category 5e, 26 AWG stranded F/UTP patch cord, RJ45 plug to RJ45 plug, 1m, Black. Includes dust caps.		
ISPTH6X1MTL	Category 6A, 600 V 26 AWG stranded SF/UTP patch cord, RJ45 plug to RJ45 plug, 1m, Teal.		
ISTPSP1MBL	Category 6, 26 AWG stranded S/UTP patch cord, RJ45 plug with bulkhead to RJ45 plug with bulkhead, 1m, Black. Includes dust caps.		
IUTPCH3BLY	Category 5e, 24 stranded U/UTP patch cord, RJ45 plug to RJ45 plug, 3 ft., Black. Includes dust caps.		
IUTPSP3BL	Category 6, 24 AWG stranded U/UTP patch cord, RJ45 plug with bulkhead to RJ45 plug with bulkhead, 3 ft., Black. Includes dust caps.		

For additional colors and lengths, refer to [www.panduit.com](http://www.panduit.com).

B1

B2

B3

C1

C2

C3

C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

**IndustrialNet™ Copper Connectors**

- IP/NEMA/UL/CE rated to ensure reliable performance in harsh factory environments
- Extended temperature range provides durable connections in extreme conditions
- Factory terminated design assures reliability and saves time
- Optional RJ45 connector speeds deployment



**ISPS5E44MFA, ISPS6A88MFA**



**ICAM12X90RJS**



**ICAM12DRJS**



**IAEBHV56XS MPSIV56XT**



**IAEBH5\*, IAEBH6\*, IAEBHC5\*, IAEBHC6\***



**MPI588T, MPSI588T**



**ISPS688FA**

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	------------------	----------------	----------------

**Industrial M12 Connectors**

<b>ISPS5E44MFA</b>	Category 5e, M12 D-Code shielded field terminable connector, male.	1	25
<b>ISPS6A88MFA</b>	Category 6A, M12 X-Code shielded field terminable connector, male.		10
<b>ICAM12X90RJS</b>	Category 6A, M12 X-Code shielded to RJ45 industrial adapter, 90° angle, panel mount.	1	15
<b>ICAM12XRJS</b>	Category 6A, M12 X-Code shielded to RJ45 industrial adapter, panel mount.		15
<b>ICAM12DRJS</b>	Category 5e, M12 D-Code to RJ45 industrial adapter, panel mount.		10

**Industrial Bulkhead Connector with Protective Cover**

<b>IAEBHV56XS</b>	Category 6A, Variant 5 IP67 rated RJ45 connector, shielded.	1	10
<b>MPSIV56XT</b>	Category 6A, Variant 5 IP67, RJ45 modular plug, shielded.		
<b>IAEBH6X</b>	Category 6A, Variant 1 IP67 rated RJ45 connector.		
<b>IAEBH6XS</b>	Category 6A, Variant 1 IP67 rated RJ45 connector, shielded.		
<b>IAEBH6</b>	Category 6, Variant 1 IP67 rated RJ45 connector.		
<b>IAEBH6S</b>	Category 6, Variant 1 IP67 rated RJ45 connector, shielded.		
<b>IAEBH5E</b>	Category 5e, Variant 1 IP67 rated RJ45 connector.		
<b>IAEBH5ES</b>	Category 5e, Variant 1 IP67 rated RJ45 connector, shielded.		
<b>MPI588T</b>	Category 5e, Variant 1 IP67 rated modular plug.		
<b>MPSI588T</b>	Category 5e, Variant 1 IP67 rated modular plug, shielded.		

**Industrial Bulkhead Coupler with Protective Cover**

<b>IAEBHC6</b>	Category 6, Variant 1 IP67 rated RJ45 coupler.	1	10
<b>IAEBHC5E</b>	Category 5e, Variant 1 IP67 rated RJ45 coupler.		

**Industrial Mini-Com® Coupler Module**

<b>IAEBHUSBAA</b>	USB 2.0 Variant 1 IP67 rated female A to female A coupler.	1	10
-------------------	--	---	----

**Industrial RJ45 Plugs**

<b>ISPS688FA</b>	Category 6A, RJ45 plug for 24-22 AWG solid, 1.0-1.6mm conductor diameter, shielded.	1	10
<b>ISPS688FAS</b>	Category 6A, RJ45 plug for 24-22 AWG stranded, 0.85-1.00mm conductor diameter, shielded.		

Order number of pieces required, in multiples of Standard Package Quantity.

## IndustrialNet™ Overmolded Cordsets

- IP/NEMA/UL/CE rated to ensure reliable performance in harsh factory environments
- Factory terminated design assures reliability and saves time
- TPE/TPU jackets protect cable, providing increased reliability in high-flex applications
- Extended temperature range provides durable connections in extreme conditions
- Rated to 10 million flex cycles
- Optional RJ45 connector speeds deployment



Part Number	Termination End 1	Termination End 2	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>Category 5e, STP Cable</b>				
ICD11T1NTL*M	M12, Male D-Code, Straight Connector	M12, Male D-Code, Straight Connector	1	10
ICD22T1NTL*M	M12, Male D-Code, Angled Connector	M12, Male D-Code, Angled Connector		
ICD14T1NTL*M	M12, Male D-Code, Straight Connector	RJ45 Modular Plug		
ICD44T1NTL*M	M12, Bulkhead, Female D-Code Connector	RJ45 Modular Plug		
ICD45T1NTL0.5M	M12, Bulkhead, Female D-Code Connector	Unterminated		
<b>Category 5e, UTP Cable</b>				
ICD11T2NTL*M	M12, Male D-Code, Straight Connector	M12, Male D-Code, Straight Connector	1	10
ICD35T2NTL*M	M12, Female D-Code, Straight Connector	Unterminated		
ICD25T2NTL*M	M12, Male D-Code, Angled Connector	Unterminated		
ICD15T2NTL*M	M12, Male D-Code, Straight Connector	Unterminated		
<b>Category 6A, STP Cable</b>				
ICX11T1NTL*M	M12, Male X-Code, Straight Connector	M12, Male X-Code, Straight Connector	1	10
ICX44T1NTL*M	M12, Bulkhead, Female X-Code Connector	RJ45 Modular Plug		
ICX45T1NTL0.5M	M12, Bulkhead, Female X-Code Connector	Unterminated		
ICX15T1NTL*M	M12, Male X-Code, Straight Connector	Unterminated		

\*A variety of standard lengths and configurations are available. Contact customer service. Representative list only. Please visit [www.panduit.com](http://www.panduit.com) for full offering.

B1

B2

B3

C1

C2

C3

C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

B1

## IndustrialNet™ Motor Control Connectivity (MCC)

B2

- Used to upgrade legacy MCCs to intelligent MCCs or to quickly connect Micro Data Centers with Industrial Distribution Frames and Network Zone Systems for holistic network connectivity

B3

- Factory terminated design assures reliability and saves time
- 100% factory tested ensures performance

- Snaps in and out of DIN rail patch panels and other Mini-Com® Products
- Each bundle is wrapped with a Kevlar\*\* band
- Cables are bundled to prevent alien cross-talk within the bundle
- Each bundle includes cable assembly identification for future traceability

C1



I4JPBJLUXX

C2

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
I4JPBJLUXX*	Category 6A plenum; jack no stagger to jack no stagger, Black.	1	—
I4KOTJLUXX*	Category 6A outdoor; jack no stagger to jack no stagger, Teal.		

\*A variety of connections and lengths in loomed and non-loomed versions available. Contact customer service.

\*\*Kevlar is a registered trademark of E.I. du Pont de Nemours and Company or its affiliates.

C3

C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

G1.6

Order number of pieces required, in multiples of Standard Package Quantity.

## Fiber Adapter and Patch Cords

- NEC 770 Compliant
- UL Approved

- LSZH cable jacket rating
- Industrial rated cable for reliable performance in harsh environments



Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
IAEF617P-7PM1	Industrial LC to LC multimode duplex patch cord - 62.5/125µm.	1	10
IAEF617P-NM1	Industrial LC to pigtail multimode duplex pigtail – 62.5/125µm.		
IAEF7JMA	Industrial LC fiber optic bulkhead adapter.		



**Industrial Accessories**

- Modular design for easy DIN rail mounting
- Compact size and low profile saves valuable DIN rail space
- Include labels for easy moves, adds and changes
- Easy installation - no special tools required



**CADIN1IG**



**CMDJAQLCZBL**



**CJ688TGBL**



**CDPP8RG**



**FDME8RG**



**IAEFP1**



**IAEFP2-2G**

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>Mini-Com® DIN Rail Mount Adapter</b>			
CADIN1IG	Single-port DIN rail mount adapter, International Gray.	1	10
CADIN1BL	Single-port DIN rail mount adapter, Black.		
CADIN1IW	Single-port DIN rail mount adapter, International White.		
CMDJAQLCZBL	Adapter module supplied with one LC Sr./Jr. OM3/OM4 duplex multimode fiber optic adapter (AQ) with zirconia ceramic split sleeves.		
CJ688TGBL	Category 6, RJ45, UTP Mini-Com® Universal Jack Module, TG-style termination, Black.		

**IndustrialNet™ DIN Rail Mount Copper Patch Panel**

CDPP8RG	8-port patch panel, DIN rail mount.	1	10
---------	-------------------------------------	---	----

**IndustrialNet™ DIN Rail Mount Fiber Enclosure**

FDME8RG	8-port fiber optic enclosure, DIN rail mount.	1	10
---------	---	---	----

**IndustrialNet™ Stainless Steel Faceplate**

IAEFP1	Vertical faceplate accepts one IndustrialNet™ Bulkhead Connector or Adapter.	1	10
IAEFP2-2G	Double gang, vertical faceplate accepts two IndustrialNet™ Bulkhead Connectors or Adapters.		



### Pre-Configured Micro Data Center (MDC)

- Pre-configured solution enables fast deployment of servers, storage, and switches for an industrial network
- Dynamic rated version ensures safe transport of IT equipment under typical shipping conditions
- Includes space for future expansion of server, storage, and related patching to allow for increased network capacity without requiring addition to control room footprint

- Bonded structure helps ensure network reliability and prevent equipment failure
- Integrated cable management with bend radius control maintains bandwidth through the network for increased uptime
- Reference architecture provides a physical map of the logical network layer following recommended installation practices to increase reliability



MDC79D and MDC79

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
MDC79D	Dynamic, single hinge perforated front door, split perforated rear doors, split side panels (2), 42 RU, network cabling, patch panels, cable management, grounding, casters, shock pallet, and ramp. Color Black. Dimensions: 79.8" H x 27.6" W x 48.0" D (2026mm x 700mm x 1200mm)	1	—
MDC79	Single hinge perforated front door, split perforated rear doors, split side panels (2), 42 RU, network cabling, patch panels, cable management, grounding, and casters. Color Black. Dimensions: 79.8" H x 27.6" W x 48.0" D (2026mm x 700mm x 1200mm)		

### Industrial Network Uninterruptible Power Supply (UPS)

- Supports industrial switches during power outages
- Ultracapacitor technology decreases downtime risk by up to 40%\*
- Maintenance-free operation contributes to 50-70% reduced cost of ownership\*
- Non-HazMat

- Remote management with auto alerts works with standard web browsers and EtherNet/IP\*\*
- Easy device monitoring through SNMP v1/V2c/V3
- Wide operating temperature range -40°C to +60°C
- Compact, one-piece design saves 50% or more DIN Rail space compared to similar UPS devices



UPS00100DC

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
UPS00100DC	Uninterruptible power supply (UPS), 100 W; no-battery, maintenance-free with remote management; 24-28 VDC in/out; DIN rail mount.	1	—
UPS003LSM	UPS load sense module; optional accessory for use in dual, redundant power supply configurations to monitor load on primary supply.		

\*Compared to battery-based UPS devices. \*\*EtherNet/IP is a trademark of ODVA.



UPS003LSM

B1

## IndustrialNet™ Data Access Port

- NEMA/UL Type 4X and Type 12, IP65 Rated
- Modular design for increased flexibility; accepts select Mini-Com® Modules including copper, fiber, USB ports, serial ports, and HMI memory components
- Integrated GFCI receptable outlet provides power to external monitoring devices, preventing downtime associated with overloading critical system components
- Locking hasp accepts Panduit lockout/tagout products or padlock to prevent unauthorized access for improved security
- Removable mounting plate accepts a variety of power supplies, providing flexibility to meet regional electrical requirements
- Meets TIA/EIA-606-A labeling standards allowing identification of data and power, reducing downtime during maintenance and trouble shooting
- Covered screw holes prevent unintentional disruption of service by unauthorized personnel and protection against arc flash, improving security, safety, and network uptime
- Pre-configured mounting template quickly and easily identifies mounting hole locations and cutouts

B2

B3

C1

C2

C3



C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
IAPNG5EWH	GFCI data access port, Category 5e coupler and blank, White.	1	—

## Network Zone Systems

- Universal design works with most DIN mount industrial Ethernet switches, providing design flexibility
- Pre-configured solution delivers up to 75% faster implementation
- Designed to accept customer supplied switches
- Copper/fiber patch fields and connectivity enable troubleshooting of network connections
- Isolation barrier segregates higher line voltage from lower voltage switch for increased safety
- Bonding provisions and grounding bar ensure path to ground to protect personnel and equipment
- Gland plate allows quick and easy access to machine ingress points into enclosure
- Detailed installation guide provides easy, repeatable design instructions, assuring consistency and saving time on the job-site
- UL Type 4/12 or 4X, UL 508A Listed, CE Approved, IP66 Rated



Z23U



Z22U



Z23C-S



Z22C-S



ZFLEX1



ZFLEX 2

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>Universal Network Zone System - Includes Power Infrastructure</b>			
Z23U-S25	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6 UTP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, maintenance-free UPS.	1	-
Z23U-S25S	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6A STP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, maintenance-free UPS.		
Z23U-S24	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6 UTP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies.		
Z23U-S24S	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6A STP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies.		
Z23U-S26	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6 UTP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, battery UPS, PoE.		
Z23U-S26S	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6A STP copper patch cords and jacks, (4) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, battery UPS, PoE.		
Z22U-S15	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6 UTP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, maintenance-free UPS.		
Z22U-S15S	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6A STP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, maintenance-free UPS.		
Z22U-S14	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6 UTP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies.		
Z22U-S14S	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6A STP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies.		
Z22U-S16	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6 UTP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, battery UPS, PoE.		
Z22U-S16S	24" x 24" mild steel enclosure, for one industrial switch, includes (8) Category 6A STP copper patch cords and jacks, (2) MM LC fiber uplink patch cords with (6) adapters and redundant power supplies, battery UPS, PoE.		
<b>Pre-Configured Network Zone Systems</b>			
Z23C-S	24" x 36" mild steel enclosure, for two industrial switches, includes (16) Category 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adapters, backplane, and cable management.	1	-
Z22C-S	24" x 24" mild steel enclosure, for two industrial switches, includes (8) Category 6 UTP copper patch cords and jacks, (2) MM LC fiber patch cords with 6 LC adapters, backplane, and cable management.		
<b>HD Flex Cassettes</b>			
ZFLEX1	Mounting bracket for one 6-port fiber cassette in network zone systems Z22X-X and Z23X-X.	1	-
ZFLEX2	Mounting bracket for two 6-port fiber cassettes in network zone systems Z22X-X and Z23X-X.		

Also available in 316 stainless steel. Refer to [www.panduit.com](http://www.panduit.com).

B1

B2

B3

C1

C2

C3

C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

## Pre-Configured Industrial Distribution Frame (IDF)

- Engineered to deploy and protect rack mount Ethernet switches in industrial applications
- Pre-configured, wall mount design delivers up to 25% faster implementation
- Defined equipment locations and cable routings incorporate Panduit best practices in connectivity, cable management, wiring, and grounding
- Additional back-end space allows for 3X the cooling capacity over typical deployments
- Key-locking handle limits access to authorized personnel for a secure network
- Detailed installation guide provides easy instructions, assuring consistency and saving time on the job-site
- UL Type 4/12 or 4/4X/12 and IP66 Rated



ZDF48-RA



ZDF242430

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
ZDF48-RA	Mild steel enclosure; 26U; for two access and two distribution switches; pre-installed with front and rear rack angles, fiber enclosure, 48-port patch panel, cable management, grounding, 10" DIN rail, (2) fiber spools, (2) back panels, (2) ESD ports, 30" length of duct, (2) duplex power receptacles, cage nuts, labeling for cable routing, strain relief bars, (4) power cables; includes ESD wrist strap, (1) hook and loop, (1) grounding cable, mounting hardware, conduit schedule, and ingress template.	1	—
ZDF48-EA	Mild steel enclosure; 26U; for two access and two distribution switches; pre-installed with front and rear rack angles, fiber enclosure, 48-port patch panel, cable management, grounding, 10" DIN rail, (2) fiber spools, (2) back panels, (2) ESD ports, 30" length of duct, cage nuts, labeling for cable routing, strain relief bars, includes ESD wrist strap, (1) hook and loop, (1) grounding cable, mounting hardware, conduit schedule, and ingress template, for EMEA/APJ.		
ZDF242430	Mild steel enclosure, 12U, for two access or two distribution switches; pre-installed with front and rear rack angles, fiber enclosure, 48-port patch panel, grounding, 10" DIN rail, (2) fiber spools, (1) back panel, (2) ESD ports, 30" length of duct, cage nuts, labeling for cable routing, strain relief bars; includes ESD wrist strap, (1) hook and loop, (1) grounding cable, mounting hardware, conduit schedule, and ingress template.		

Also available in 316 stainless steel. Refer to [www.panduit.com](http://www.panduit.com).

## Wireless Enclosures

- Accommodates the most popular Wireless Access Points
- Fiberglass construction and aluminum mounting plate allow quick and easy access point installation
- Provisions for padlocks to protect against tampering and theft
- Includes pre-configured mounting template and connectivity kit with 2-position outlet box, Mini-Com® TX6™ PLUS Jack Module, TX6™ PLUS patch cord, silicone sealant, and grounding cable
- UL 508A Listed, NEMA 4X and IP66 Rated



PZNWE12



PZNWE14

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PZNWE12	Wireless enclosure designed for Power over Ethernet applications. Includes UTP connectivity kit and pre-configured mounting template. External dimensions: 13.56" H x 13.47" W x 6.56" D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70" H x 11.70" W x 6.29" D (297.2mm x 297.2mm x 159.8mm).	1	—
PZNWE14	Wireless enclosure designed for traditional AC power applications. Includes UTP connectivity kit and pre-configured mounting template. External dimensions: 15.50" H x 13.50" W x 6.25" D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53" H x 11.55" W x 5.94" D (343.7mm x 293.4mm x 150.9mm).		

Shielded connectivity kit, NEMA 4X rated fittings, and NEMA 4X drain and vent kit available. Refer to [www.panduit.com](http://www.panduit.com).