

Crimping pliers - CRIMPFOX 10T-F - 1134913

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, type of contact: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 0.14 mm², max. cross section: 10 mm², For TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, frontal insertion, compression: Trapezoidal crimp, black

Your advantages

- ✓ Comfortable to use, thanks to low grip span with optimum manual force progression
- ✓ Suitable for TWIN ferrules, thanks to continuous automatic adjustment
- ✓ Large cross section range from 0.14 mm² ... 10 mm²
- ✓ Process reliability, thanks to pressure lock and self-adjusting die



Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 067168
GTIN	4063151067168
Weight per Piece (excluding packing)	380.000 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	180 mm
Width (a)	65 mm
Height (c)	25 mm

General

Crimping pliers - CRIMPFOX 10T-F - 1134913

Technical data

General

Color	black
Compression	Trapezoidal crimp
Type of contact	Insulated and uninsulated ferrules
Designation	Crimping position 1
Min. cross section	0.14 mm ²
Max. cross section	10 mm ²
AWG min	26
AWG max	8
Weight	302 g
Min. cross section	0.14 mm ²
Max. cross section	10 mm ²
AWG min	26
AWG max	8

Classifications

eCl@ss

eCl@ss 6.0	21043800
eCl@ss 7.0	21043811
eCl@ss 9.0	21043811

ETIM

ETIM 6.0	EC000168
ETIM 7.0	EC000168

Accessories

Accessories

Mounting material

Replacement spring - CRIMPFOX/ SPR-4 - 1200288



Spare recuperating spring

