

Process Gas Diaphragm Valve

Series AZ

RoHS

Cleaned for high purity semiconductor applications.

Cleanroom assembled and He leaked tested.

Valve meets dimensional requirements of

SEMI F36-0299, Option I.

Manually Operated Type

Series AZ3652 and 4652

- Compact and lightweight by modifying the knob design
- The knob is a unique design that combines a scalloped round knob with a raised rectangular section to provide two choices of gripping.

Actuation is 90 degrees open to closed with a cutout window, on both sides of raised rectangular section, providing visual status of open or closed state.

Direction of a raised rectangular section indicate open/close status



Height

57 mm

Weight

240g



Air Operated Type

Series AZ3542 and 4542

- Compact and lightweight by making the actuator shorter
- M5 actuation port

Height

55 mm

Weight

220g

ATech

SVC

1107

AP

SL

AZ

AK

BP

Series AZ

Air operated type

Series AZ3542/AZ4542



Body material

316L SS

Electropolish and passivation internals

SEMI standard

Mounting hole, dimension, and face to face dimension are interchangeable (Guide for Dimensions and Connections of Gas Distribution Components).

Multiple port available in various configurations


	Machined		Welded		
Body					
Connection	Face seal fitting (Male)	Tube weld (Tube stub)	Face seal fitting (Male)	Face seal fitting (Female)	Tube weld (Tube stub)
Connection size (inch)	1/4, 3/8	1/4, 3/8, 1/2	1/4, 3/8		
Interchangeability	No		Yes		

Welded type, inlet and outlet available with any combination of fitting type and size.

Further information ▶▶▶ How to order P.1110, 1112



Example)

Outlet
Face seal fitting (Male) 1/4





Inlet
Face seal fitting (Female) 3/8

Air operated type

 	Series	Status	Body material	Max. operating pressure (MPa)	Cv * 1)	Connections	Page
						Fitting	
Machined type Welded type	AZ3542	N.C.	316L SS	0.9	0.29	Face seal fitting	P.1110
	AZ4542					Tube weld	

Manually operated type

 	Series	Knob	Body material	Max. operating pressure (MPa)	Cv * 1)	Connections	Page
						Fitting	
Machined type Welded type	AZ3652	Knob with a raised section on top (indication window)	316L SS	1.7	0.29	Face seal fitting	P.1112
	AZ4652					Tube weld	

* 1) Cv calculation based on SEMI Standard



Manually operated type

Series AZ3652/AZ4652



User-friendly forged body

Rounded corner for safety and easy operation (forged body is for machined type.)

Port



Machined type

Welded type

Welded type, ports (2, 3, 4 ports) and porting configuration (flow direction 2, 3, 4) selectable

Further information ▶▶▶ Optional porting configuration P.1114



Series AZ

Applicable Fluid

Precautions for selection

The proper regulator and valve selection can be significantly affected by parameters such as system design, flow duration, frequency of use, ambient conditions and outlet pressure. It is important to understand that one may follow this guide's recommendation, yet have a failure due to a parameter specific to the given application, as noted.

Applicable Fluid

Process Gas	Molecular Formula
Boron11 Trifluoride	11BF ₃
Argon	Ar
Arsine	AsH ₃
Boron Trichloride	BCl ₃
Boron Trifluoride	BF ₃
Halocarbon114	C ₂ ClF ₄
Halocarbon115	C ₂ ClF ₅
Halocarbon116	C ₂ F ₆
Acetylene	C ₂ H ₂
Halocarbon134A	C ₂ H ₂ F ₄
Ethylene	C ₂ H ₄
Halocarbon125	C ₂ HF ₅
Dimethylsilane	C ₂ SiH ₆
HalocarbonR218	C ₃ F ₈
Propene	C ₃ H ₆
Propane	C ₃ H ₈
Perfluoro-butadiene	C ₄ F ₆
HalocarbonC318	C ₄ F ₈
Butene-1	C ₄ H ₈
Octafluorocyclopentene	C ₅ F ₈
Halocarbon12B2	CB ₂ F ₂
Halocarbon13B1	CBrF ₃
Halocarbon12	CCl ₂ F ₂
Halocarbon13	CClF ₃
Halocarbon14	CF ₄
Halocarbon32	CH ₂ F ₂
Trimethylsilane	(CH ₃) ₃ SiH
Methyl Chloride	CH ₃ Cl
Methyl Fluoride	CH ₃ F
Methanol	CH ₃ OH
Methylsilane	CH ₃ SiH ₃
Methane	CH ₄
Halocarbon21	CHCl ₂ F
Halocarbon23	CHF ₃

Process Gas	Molecular Formula
Chlorine	Cl ₂
Chlorine Trifluoride	ClF ₃
Carbon Monoxide	CO
Carbon Dioxide	CO ₂
Germane	GeH ₄
Hydrogen	H ₂
Hydrogen Sulfide	H ₂ S
Hydrogen Selenide	H ₂ Se
Hydrogen Bromide	HBr
Hydrogen Chloride	HCl
Helium	He
Hydrogen Fluoride	HF
Krypton	Kr
Nitrogen	N ₂
Nitrogen Oxide	N ₂ O
Neon	Ne
Nitrogen Trifluoride	NF ₃
Ammonia	NH ₃
Nitric Oxide	NO
Oxygen	O ₂
Phosphorous Pentafluoride	PF ₅
Phosphine	PH ₃
Sulfer Tetrafluoride	SF ₄
Sulfer Hexafluoride	SF ₆
Disilane	Si ₂ H ₆
Silicon Tetrachloride	SiCl ₄
Silicon Tetrafluoride	SiF ₄
Dichlorosilane	SiH ₂ Cl ₂
Silane	SiH ₄
Trichlorosilane	SiHCl ₃
Sulfur Dioxide	SO ₂
Diethyltelluride	Te (C ₂ H ₅) ₂
Tungsten Hexafluoride	WF ₆
Xenon	Xe

- This applicable fluid is a reference guide and does not apply to product guarantee.
- Please consult SMC for a specific recommendation beyond the scope of this document.

Caution

Since the product specified here is used under various operating conditions, its compatibility with fluid and specific equipment must be decided by the person who designs the equipment or decided its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product regardless of any recommendation. Proper installation, operation and maintenance are also required to assure safe, trouble free performance.



AP

SL

AZ

AK

BP

Diaphragm Valve for Ultra High Purity

Air operated type

Series AZ3542 & 4542

- Suitable for UHP gas supply line
- Body material: 316L SS
- Pneumatically actuated normally closed



How to Order

ROHS

(Inlet) (Outlet)

AZ 3 542 S 2P MV4 MV4

Size

Code	Cv
3	0.29
4	0.5

Model

Code	Status	Maximum operating pressure
542	Normally closed (N.C.)	125 psig (0.9 MPa)

Material

Code	Body material
S	316L SS

Ports

Code	Ports	Connection
2P	2 ports	Machined
2PW		Welded

Optional portings and porting configurations available.
Please refer to page 1114.

Seat material

Code	Material
No code	PCTFE (Standard)
VS	Polyimide

Connections

Code	Connections	Size Port	AZ3		AZ4	
			2P	2PW	2P	2PW
MV4	1/4 inch face seal (Male) *1)	●	○	●	○	
FV4	1/4 inch face seal (Female)		○		○	
TW4	1/4 inch tube weld	●	○			
MV6	3/8 inch face seal (Male) *1)				●	
FV6	3/8 inch face seal (Female)				○	
TW6	3/8 inch tube weld				●	
TW8	1/2 inch tube weld				●	

● Only available with the same type fittings inlet and outlet.
○ Inlet and outlet available with any combination of fitting type and size.
* 1) Fixed fitting (no rotating nut)


Specifications

Operating Parameters		AZ3542	AZ4542
Status		Normally closed (N.C.)	
Gas		Select compatible materials of construction for the gas	
Operating pressure		Vacuum to 125 psig (0.9 MPa)	
Proof pressure		200 psig (1.4 MPa)	
Burst pressure		375 psig (2.7 MPa)	
Ambient and operating temperature		-10 to 71°C (No freezing)	
Cv		0.29	0.5
Leak rate	Inboard leakage	2 x 10 ⁻¹¹ Pa·m ³ /s	
	Outboard leakage	2 x 10 ⁻¹⁰ Pa·m ³ /s *1)	
Across the seat leak		4 x 10 ⁻⁹ Pa·m ³ /s *1)	
Surface finish		Ra 10µin. (0.25 µm)	
Connections		Face seal, Tube weld	
Actuation pressure		60 to 110 psig (0.4 to 0.76 MPa)	
Actuation port connection		M5 x 0.8	
Actuation port location		Top	
Installation		Bottom mount	
Internal volume		0.06 in ³ (1.07 cm ³)	
Weight		0.24 kg *2)	

* 1) Tested with Helium gas inlet pressure 125 psig (0.9 MPa).

* 2) Weight for AZ3542S2PMV4MV4 including individual boxed weight. It may vary depending on connections or options.

Construction



Diaphragm Valve for Ultra High Purity *Series AZ3542 & 4542*


Air operated type

Dimensions


inch (mm)

AZ3542 & 4542


Ports: 2P (Machined)



Connections: MV□




Connections: TW□




Note) MV6 is bar stock body.

Ports	Connections	A	
		inch	(mm)
2P (Machined)	MV4	1.14	(29.0)
	TW4	0.875	(22.2)
	MV6	1.5	(38.1)
	TW6	0.875	(22.2)
	TW8	1.125	(28.6)


Ports: 2PW (Welded)



Connections: MV□, FV□



Connections: TW□



Ports	Connections	A		B
		inch	(mm)	
2PW (Welded)	MV4	1.39	(35.3)	1.12 sq. (28.4)
	FV4			
	TW4	1.06	(26.9)	
	MV6	1.93	(49.0)	
	TW6	1.325	(33.7)	

AP

SL

AZ

AK

BP

Diaphragm Valve for Ultra High Purity

Manually operated type

Series AZ3652 & 4652

- Suitable for UHP gas supply line
- Body material: 316L SS



RoHS

How to Order

AZ **3** **652** **S** **2P** **MV4** **MV4**

(Inlet) (Outlet)

Size

Code	Cv
3	0.29
4	0.5

Model

Code	Knob	Maximum operating pressure
652	1/4 turn indicating round knob with a raised rectangular section	250 psig (1.7 MPa)

Material

Code	Body material
S	316L SS

Ports

Code	Ports	Connection
2P	2 ports	Machined
2PW		Welded

Optional portings and porting configurations available. Please refer to page 1114.

Seat material

Code	Material
No code	PCTFE (Standard)
VS	Polyimide

Connections

Code	Connections	Size Port	AZ3		AZ4	
			2P	2PW	2P	2PW
MV4	1/4 inch face seal (Male) *1)	●	○	●	○	
FV4	1/4 inch face seal (Female)		○		○	
TW4	1/4 inch tube weld	●	○			
MV6	3/8 inch face seal (Male) *1)				●	
FV6	3/8 inch face seal (Female)				○	
TW6	3/8 inch tube weld				●	
TW8	1/2 inch tube weld				●	

●: Only available with the same type fittings inlet and outlet.

○: Inlet and outlet available with any combination of fitting type and size.

* 1) Fixed fitting (no rotating nut)


Specifications

Operating Parameters		AZ3652	AZ4652
Gas		Select compatible materials of construction for the gas	
Operating pressure		Vacuum to 250 psig (1.7 MPa)	
Proof pressure		375 psig (2.6 MPa)	
Burst pressure		750 psig (5.1 MPa)	
Ambient and operating temperature		-40 to 71 °C (No freezing)	
Cv		0.29	0.5
Leak rate	Inboard leakage	2 x 10 ⁻¹¹ Pa·m ³ /s	
	Outboard leakage	2 x 10 ⁻¹⁰ Pa·m ³ /s *1)	
Across the seat leak		4 x 10 ⁻⁹ Pa·m ³ /s *1)	
Surface finish		Ra 10 μin. (0.25 μm)	
Connections		Face seal, Tube weld	
Installation		Bottom mount	
Internal volume		0.06 in ³ (1.07 cm ³)	
Weight		0.22 kg *2)	
Knob		1/4 turn indicating round knob with a raised rectangular section	

* 1) Tested with Helium gas inlet pressure 125 psig (0.9 MPa).

* 2) Weight for AZ3652S2PMV4MV4 including individual boxed weight. It may vary depending on connections.

Construction



Wetted Parts Material

Wetted Parts	S
Body	316L SS
Surface finish	Electropolish + Passivation
Diaphragm	Ni-Co Alloy
Seat	PCTFE (Option: Polyimide)

Diaphragm Valve for Ultra High Purity *Series AZ3652 & 4652*



Manually operated type

Dimensions


inch (mm)

AZ3652 & 4652


Ports: 2P (Machined)



Connections: MV□





Connections: TW□




Note) MV6 is bar stock body.

Ports	Connections	A	
		inch	(mm)
2P (Machined)	MV4	1.14	(29.0)
	TW4	0.875	(22.2)
	MV6	1.5	(38.1)
	TW6	0.875	(22.2)
	TW8	1.125	(28.6)


Ports: 2PW (Welded)



Connections: MV□, FV□



Connections: TW□



Ports	Connections	A		B	
		inch	(mm)	inch	(mm)
2PW (Welded)	MV4	1.39	(35.3)	1.12 sq.	(28.4)
	FV4				
	TW4	1.06	(26.9)		
	MV6	1.93	(49.0)		
	TW6	1.325	(33.7)		

AP

SL

AZ

AK

BP



Made to Order

Optional knob color available. Red, blue, green, gold, silver, purple, etc.
Please contact SMC for further information.



Series AZ / Diaphragm Valve Optional Porting Configuration

How to Order

① ② ③ ④

AZ 3652 S 4PWW MV4 TW4 FV4 FV4

Size

Code	
3542	
4542	
3652	
4652	

Material

Code	Body material
S	316L SS

Seat material

Code	Material
No code	PCTFE (Standard)
VS	Polyimide

Connections (number indicates the port location)

Code	Connections	AZ3	AZ4
MV4	1/4 inch face seal (Male *1)	○	○
FV4	1/4 inch face seal (Female)	○	○
TW4	1/4 inch tube weld	○	
MV6	3/8 inch face seal (Male *1)		○
FV6	3/8 inch face seal (Female)		○
TW6	3/8 inch tube weld		○

○: Available with any combination of fitting type and size.
* 1) Fixed fitting

Ports

Code	Ports	Configuration	Connections
2PW		Refer to the port configuration	Welded
2PWA	2 ports		
2PWC			
3PWD		3 ports	
3PWG			
3PWE			
4PWW	4 ports		

All multiple port options are welded type.
Please refer to the welded type for dimensions.

Port Configuration

- Valves are illustrated top view looking down through the valve.
- Inlet (Upstream) is defined as a port connected to the region below the valve seat. It is illustrated with an arrow pointing towards the valve body or an "empty" triangle on the schematic. Outlet (Downstream) is defined as a port connected to the region above the seat and below the diaphragm. It is illustrated with an arrow pointing away from the valve body or a "filled" triangle on the schematic.
- The traditional flow direction is INLET to OUTLET, but AP Tech valves may be employed in either flow direction.
- End connections are specified in numerical order per the diagram's numbered arrows.

